

Declaration of Performance



Sunseeker Windows Ltd
72 – 84 Station Road
Burton Latimer
Northants
NN15 5NX

16

DoP No: 1- 08/08/16

**HALO System 10 Internally Glazed Casement Window,
Intended for use in domestic or commercial refurbishment or new building applications.**

Annex ZA.1 of BS EN 14351-1:2006+A1:2010

Water tightness: No Performance Determined

Dangerous substances: None released under normal indoor use.

Resistance to wind load: No Performance Determined

Load-bearing capacity of safety devices: Pass, 350N when fitted (1)

Acoustic performance: No Performance Determined

Thermal transmittance: No worse than 1.6 W/m²k (2)

Radiation Properties: No Performance Determined

Air permeability: No Performance Determined

A Factory Production Control (FPC) system is established, documented and maintained in accordance with AVCP System 3 as per Annex ZA.2 of BS EN 14351-1:2006+A1:2010.

(1) Report No. 2370/7479366/1 of 3 dated 27/01/2010 for Safety & Security friction hinges with built in restrictor - Notified Test Body BSI No. 0086

(2) Thermal Transmittance calculation approved by Buildcheck Notified Test Body No. 1086 Report No. CU13238-1 dated 18/06/2013.

Jeremy Cattell

Sunseeker Windows Ltd

Managing Director

08/08/2016