

Declaration of Performance



Sunseeker Windows Ltd
72 – 84 Station Road
Burton Latimer
Northants
NN15 5NX

20

DoP No: 2- 28/07/2020

Open-in and Open-out glazed PVCu Entrance Doors Intended for use in domestic or commercial refurbishment or new building applications.

Annex ZA.1 of BS EN 14351-1:2006+A1:2010

Watertightness: No Performance Determined

Dangerous substances: None released under normal indoor use.

Resistance to wind load: No Performance Determined

Impact resistance (glazed doors with injury risk only): No Performance Determined

Load-bearing capacity of safety devices: None fitted

Height & width (clear opening): No Performance Determined

Acoustic performance: No Performance Determined

Thermal transmittance: No worse than 1.6 W/m²k (1)

Radiation Properties: No Performance Determined

Air permeability: No Performance Determined

A Factory Production Control (FPC) system is established, documented and maintained in accordance with AVCP System 3 as per Annex ZA.2 of BS EN 14351-1:2006+A1:2010.

(1) Thermal Transmittance calculation approved by Buildcheck, Notified Test Body No. 1086, Report No. CU13238-7, dated 20/06/2013.

Jeremy Cattell

Sunseeker Windows Ltd

Managing Director

28/07/2020