

Declaration of Performance



Sunseeker Windows Ltd
72 – 84 Station Road
Burton Latimer
Northants
NN15 5NX

0425

16

DoP No: 3- 08-08-16

**HALO System 10 Open-out Residential Door, fitted with emergency exit panic hardware
Intended for use in domestic and commercial refurbishment or new building applications on
escape routes.**

Annex ZA.1 of BS EN 14351-1:2006+A1:2010

Water tightness: No Performance Determined

Dangerous substances: None released under normal indoor use.

Resistance to wind load: No Performance Determined

Impact resistance (glazed doors with injury risk only): No Performance Determined

Height & width (clear opening): No Performance Determined

**Ability to release (locked doors on escape routes only): Emergency exit panic hardware
complies with EN 1125:2008. Notified Body 0425 issued the EC Certificate. (1)**

Acoustic performance: No Performance Determined

Thermal transmittance: No worse than 1.6 W/m²k (2)

Radiation Properties: No Performance Determined

Air permeability: No Performance Determined

(1) Continuous surveillance of Factory Production Control (FPC) in compliance with AVCP System 1 as per Annex ZA.2 of BS EN 14351-1:2006+A1:2010 by BSI Notified Test Body No. 0090,

(2) Thermal Transmittance calculation approved by Buildcheck Notified Test Body No. 1806 Report No.CU13238-7 dated 20/06/2013.

Jeremy Cattell

Managing Director

Sunseeker Windows Ltd

08/08/2016.