

# Declaration of Performance



Sunseeker Windows Ltd  
72 – 84 Station Road  
Burton Latimer  
Northants  
NN15 5NX

0425

23

DoP No: 3. 20/03/2023

**HALO System 10 Open-out Residential Door, fitted with emergency exit panic hardware  
Intended for use in domestic and commercial refurbishment or new building applications on  
escape routes.**

**Annex ZA.1 of BS EN 14351-1:2006+A1:2010**

**Water tightness: No Performance Determined**

**Dangerous substances: None released under normal indoor use.**

**Resistance to wind load: No Performance Determined**

**Impact resistance (glazed doors with injury risk only): No Performance Determined**

**Height & width (clear opening): No Performance Determined**

**Ability to release (locked doors on escape routes only): Emergency exit panic hardware  
complies with EN 1125:2008. Notified Body 0425 issued the EC Certificate. (1)**

**Acoustic performance: No Performance Determined**

**Thermal transmittance: No worse than 1.6 W/m<sup>2</sup>k (2)**

**Radiation Properties: No Performance Determined**

**Air permeability: No Performance Determined**

(1) Continuous surveillance of Factory Production Control (FPC) in compliance with AVCP System 1 as per Annex ZA.2 of BS EN 14351-1:2006+A2:2016 by BlueSky. Notified Test Body No. 2731,

(2) Thermal Transmittance calculation approved by Buildcheck Notified Test Body No. 1806 Report No.CU13238-7 dated 20/06/2013.

Jeremy Cattell

Managing Director

Sunseeker Windows Ltd

20/03/2023