

# Declaration of Performance



Sunseeker Windows Ltd  
72 – 84 Station Road  
Burton Latimer  
Northants  
NN15 5NX

16

DoP No: 5: 08/08/16

**HALO System 10 Internally Unglazed Casement Window,  
Intended for use in domestic or commercial refurbishment or new building applications.**

**Annex ZA.1 of BS EN 14351-1:2006+A1:2010**

**Water tightness: No Performance Determined**

**Dangerous substances: None released under normal indoor use.**

**Resistance to wind load: No Performance Determined**

**Load-bearing capacity of safety devices: Pass, 350N when fitted (1)**

**Acoustic performance: No Performance Determined**

**Thermal transmittance: No Performance Determined (2)**

**Radiation Properties: No Performance Determined**

**Air permeability: No Performance Determined**

**A Factory Production Control (FPC) system is established, documented and maintained in accordance with AVCP System 3 as per Annex ZA.2 of BS EN 14351-1:2006+A1:2010.**

**(1) Report No. 2370/7479366/1 of 3 dated 27/01/2010 for Safety & Security friction hinges with built in restrictor - Notified Test Body BSI No. 0086**

**(2) Thermal Transmittance has not been calculated on this unglazed product.**

Jeremy Cattell

Sunseeker Windows Ltd

Managing Director

08/08/2016.